

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Data transmission cables and systems**

with type designation(s)

**Coaxial cable Type RG 58 Marine SHF1 without armour,  
Coaxial cable Type RG213 Marine SHF1 without armour,  
Coaxial cable Type RG214 Marine SHF1 without armour**

Issued to

**APS Cables & Connectors Oy  
Rovaniemi, Finland**

is found to comply with

**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Coaxial cable 50 Ohm. Unarmoured.****Products approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.**Issued at **Høvik** on **2018-10-12**for **DNV GL**This Certificate is valid until **2023-10-11**.DNV GL local station: **Helsinki**Approval Engineer: **Ivar Bull**

---

**Marta Alonso Pontes  
Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.  
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-029785-1**  
Certificate No: **TAE0000373**

## Product description

Type RG 58 Marine SHF1 without armour,  
Type RG213 Marine SHF1 without armour,  
Type RG214 Marine SHF1 without armour

### Type RG 58 Marine SHF1 without armour

Construction	
Inner Conductor	Tinned Copper 19x 0,18mm
Insulation	Low density polyethylene
Shield	Aluminium+Polyester+Aluminium tape
Outer conductor	Tinned copper braid
Sheath	SHF1
Outer diameter	8,0 $\pm$ 0,2 mm

### Type RG213 Marine SHF1 without armour

Construction	
Inner Conductor	Plain copper 7x0,75mm
Insulation	Low density polyethylene
Shield	Aluminium+Polyester+Aluminium tape
Outer conductor	Tinned copper braid
Sheath	SHF1
Outer diameter	10,30 $\pm$ 0,18 mm

### Type RG214 Marine SHF1 without armour

Construction	
Inner Conductor	Silvered copper 7x0,75mm
Insulation	Low density polyethylene
Shield	Aluminium+Polyester+Aluminium tape
1st outer conductor	Silvered copper braid
2 <sup>nd</sup> outer conductor	Silvered copper braid
Sheath	SHF1
Outer diameter	10,80 $\pm$ 0,18mm

For electrical data and transmission properties, please refer to relevant datasheets.

## Manufactured by

DNV GL Id. 10310952

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

## Type Approval documentation

Datasheets : APS datasheets dated 1/10/2018 and 2/10/2018.

Test reports: 2014.2301/05 dated 23.01.2014  
2014.2301/09 dated 23.01.2014  
2014.2301/11 dated 23.01.2014

## Tests carried out

Standard	Release	General description	Limitation
IEC 60096-0-1 Ed 3	2012	Radio frequency cables Part 0-1: Guide to the design of detail specifications Coaxial cables	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60332-3-24	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C	Bunch test Category C
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 61034-1/2	2013-07 2013-09	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke: Light transmittance ≥60%

## Marking of product

APS –RG 58 CU Marin SHF1 - DNVGL – IEC 60332-3-24 – <batch no.> - <meter marking>  
APS –RG 58 CU Marin SHF1 - DNVGL – IEC 60332-3-24 – <batch no.> - <meter marking>  
APS – RG 214 U Marin SHF1 – DNVGL – IEC 60332-3-24 – <batch no.> – <meter marking>

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine tests (RT) and selected type tests (ref. to applicable class programs) checked (if not available these tests shall be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE